



M-DRIVER-30-CV

LIGHTING DRIVER SOLUTIONS

Metro ELV Constant Voltage*, Class 2, Dimmable LED Drivers (30W, 24/12 V DC). Fireproof, Environmentally friendly PC cover. Short Circuit and overload protected. Integral wiring compartment.

* Constant Current Versions are available, not shown.

Features:

Input Voltage	100-120 VAC
Output Voltage	24 V DC
Output Power	30W
AC Frequency	50-60 Hz
Power Factor	>.95
Operating Temp	-30°C - 45°C
Efficiency	>85%
Lifetime	>50,000 hrs. @ Tc Max
Length	4.21" (107.000mm)
Width	1.61" (41.000mm)
Height	0.87" (22.000mm)

- FIREPROOF, ENVIRONMENTALLY FRIENDLY PC COVER
- CLASS 2
- ETL LISTED
- SHORT CIRCUIT AND OVERLOAD PROTECTED
- INTEGRAL WIRING COMPARTMENT
- TRIAC, FORWARD & REVERSE PHASE DIMMING COMPATIBLE
- 120 VAC CORD & PLUG
- 20 AWG LOW VOLTAGE LEAD WIRE WITH BARREL JACK

M-DRIVER-30-CV



120 V AC WIRING COMPARTMENT

24 V DC WIRING COMPARTMENT